



4183 FORREST ST.
 P.O. BOX 665
 OSCODA, MI. 48750
 Tel: 989-739-5157
 Fax: 989-739-2913
 Toll free: 877-227-6996
www.tip-topscrew.com

Roof-Top #12

Medium-Duty Fastener

The Roof-Top #12 medium-duty fastener is designed as a multipurpose fastener. With its spade point it can be used in light to medium steel decking (up to 24 gauge steel), wood, and in a wide range of other material. Available in lengths from 1 5/8" to 8" with a #3 phillips drive.

Application:	Approved Uses:
ROOF-TOP #12 Medium-Duty Fasteners must penetrate the steel deck a minimum of 1/3" to 1".	ROOF-TOP #12 Medium-Duty Fasteners are designed to attach wood, single-ply membrane, and insulation to medium-gauge steel (24 Gauge).

Physical Data:		Length	Thread	Quantity
Each Roof-Top #12 Fastener meets these specifications:		1.625"	Full	1,000
Thread Diameter:	.205	2.25"	Full	1,000
Shank Diameter:	.164	2.875"	Full	1,000
Threads per Inch	16	3.25"	Full	1,000
Head Diameter	.438	3.75"	Full	1,000
Head Single	Truss Head	4.5"	3 7/8"	1,000
Coating	PPG Powercron ® 8000	5"	3 7/8"	1,000
Drive/Point	#3 Phillips/Spade Point	6"	3 7/8"	1,000
		7"	3 7/8"	500
		8"	3 7/8"	500

Drive bit included in each container (sizes up to 6" in length). Available in a 50-count plastic pack.

The corrosion-resistant coating exhibits less than 15% red rust after 25 Kesternich cycles, exceeding F.M. approval standard 4470.

SHEAR STRENGTH	1" Embedment	1890 lbs.
----------------	--------------	-----------

