



4183 FORREST ST.
P.O. BOX 665
OSCODA, MI. 48750
Tel: 989-739-5157
Fax: 989-739-2913
Toll free: 877-227-6996
www.tip-topscrew.com

Roof-Top #14 Heavy-Duty Fastener

The Roof-Top #14 heavy-duty roofing fastener is available with a spade point and #3 Phillips drive that is ideal for up to 22-gauge steel. Roof-Top #14 Phillips drive/drill-point heavy-duty fasteners are ideal for up to 18-gauge steel and in all wood roof decks. The Roof-Top product line is available in lengths from 1.5" to 12". This screw also has a multitude of other uses such as pole barns, log homes, and landscaping, just to name a few.

Application:	Approved Uses:
ROOF-TOP #14 Heavy-Duty Fasteners must penetrate the steel deck a minimum of 1/3" to 1".	ROOF-TOP #14 Heavy-Duty Fasteners are designed to attach wood, single-ply membrane, and insulation to heavy gauged steel. (Spade Point-22; Gauge Drill Point- 18 Gauge)

Physical Data:				
Each Roof-Top #14 Fastener contains the same specifications.		Length	Thread	Quantity
Thread Diameter:	.237 nom.	1.5"	Full	1,000
Shank Diameter:	.180	2"	Full	1,000
Threads per Inch	13	2.5"	Full	1,000
Head Diameter	.438	3"	Full	1,000
Coating	PPG Powercron® 8000	3.5"	Full	1,000
Drive/Point	#3 Phillips Drive/Spade Point	4"	3 7/8"	1,000
Drive/Point	#3 Phillips Drive/Drill Point	4.5"	3 7/8"	1,000
Drive bit included in each container: Available in a 50-count plastic pack (sizes up to 6" lengths)		5"	3 7/8"	1,000
		5.5"	3 7/8"	1,000
		6"	3 7/8"	1,000
		7"	3 7/8"	500
		8"	3 7/8"	500
		9"	3 7/8"	500
		10"	3 7/8"	500
		11"	3 7/8"	500
		12"	3 7/8"	500

The corrosion resistant coating exhibits less than 15% red rust after 25 Kesternich cycles, exceeding F.M. approval standard 4470.

Pull-Out	
22 Ga steel deck	576 lb
3/4" plywood	556 lb
Structural concrete	743 lb

